- 5- Four, 4, layers PCB design, inner layers are GND planes.
- 6- Accessible GND test point, The test point is connected to inner GND planes as well as the connector's shield.
- 7- Ease of interface with single channel and differential scope probes.
- 8- Flying lead wire assembly may be used for board to board interface See ordering information

Electrical: Insertion loss > -3dB @6GHz

Trace impedance: 50 Ω

Operating Temperature: -55°C to +125°C

Samtec Connector:

Onboard Connector: LSHM-DH Shielded - 2 rows per 05 pins/row

Mates with: Any Samtec LSHM -DV -DH -RH formfactor Hermaphroditic connector

Pitch: 0.020" (0.50mm) pin to pin pitch

Plating: 10u" (0.25um)

Header:

Pitch: 0.1" (2.54mm) pin to pin pitch Pin: Square 0.025" (0.635mm)

Height: 0.24" (6mm) Plating: Gold Flash

Application: Manufacturing test measurement & re-use, bringup, testing, debugging

Mates with: Samtec Rugged Hermaphroditic Razor Beam LSHM


Mates with any height & formfactor LSHM connector / cable assembly

LSHM-105-01-F-DV-A-S LSHM-105-01-L-DV-A-S LSHM-105-01-F-DH-A-S LSHM-105-01-L-DH-A-S

Breakout Access: All ZX118LSHM-05 breakout adapters provide access

to ALL Samtec LSHM connector via onboard headers.

ZX118LSHM-xx simplified cross section diagram



LSHM signals path to Shunts and to/from ERF5.



ISO2001 certified RoHs - Lead Free EU RoHS2 UL E111594 document ELV- Vehicle Directive (Directive 2000/EC) European Union Directive (203/11/EC) Halogen Free per IEC-61249-2.21: 2003 RoHs Directive 2011/65/EU WEEE Directive (2012/12/EU)

Certificate of Compliance for Asbestos Certificate of Compliance for Ozone Depleting Substances, ODS Certificate REACH SVHC Certificate of Compliance RoHS EN CoC

DESCRIPTION:

WWW.ZEBAX.COM

ZX118LSHM-05 package includes:

Quantity

Samtec rugged LSHM Hermaphroditic Razor Beam Breakout Adapter

ITEM: ZX118LSHM-05

ASSEMBLY DRAWING

2.24"(57.00mm) 2.36"(60.10mm)

CHECKED:

DRAWN: M. MAHIN

Description

ALL ZEBAX products are RoHS compliant and Lead Free unless otherwise indicated

ZEBAX TECHNOLOGIES

SANTA CRUZ, CA U.S.A (831) 2 2 2 - 0717

Breakout Adapter module

Flying leads wire assembly

ZX100ACC-SS site page for ordering additional flying leads wire assembly **B**

REVISSION: 1.0

such as DV (Straight) DH (Right Angle) or RH (Reverse Right Angle).

LSHM-105-01-F-RH-A-S LSHM-105-01-L-RH-A-S

Compliance:

Certificate of Compliance for Radioactive substances

SPECIFIED DIMENSIONS ARE INCHES (MM). ROHS COMPLIANT

ALL ZEBAX TECHNOLOGIES DESIGN SPECIFICATIONS, DRAWINGS, PUBLICATIONS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." ZEBAX MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NO INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, Zebax Technologies assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. Specifications mentioned in this publication are subject to change without notice. This publication replaces all other information previously supplied. Zebax Technologies products are not authorized as in life support devices or systems

Part number

ZX118LSHM-05


ZX100ACC-SS

KADIJEH SHEET: 1 OF 3

Product Name: ZX118LSHM-05 Samtec Breakout Adapter Rugged Hermaphroditic Razor Beam - Page 2 of 3

LSHM Hermaphroditic connector mating configuration: LSHM connector is Hermaphroditic, self mating connector series, therefore ZX118LSHM-05 module would be transparent to any design using LSHM -DV or -DH connector series. Please see figure 2.1 exhibiting "Mated pin configuration details". ZX118LSHM-05 utilizes LSHM-DH connector series where the J1 LSHM connector pin 1 is connected to the J2 LSHM connector pin 2. When the ZX118LSHM-05 is mated with Host & Target (Host & Target using -DV or -DH connector series), it would be transparent since the ZX118LSHM-05 does pin swapping between the onboard LSHM connectors. If using LSHM-RH connector series, please use figure 2.2 as reference identifying pin numbering on your host

Figure 2.1: ZX118LSHM-05 mated pin configuration details





Mating configuration is with LSHM-DV on HOST


ZX118LSHM-05 Pin numbering: The listed Shunts pin numbering are listed as reference to the host LSHM connector. Since the ZX118LSHM-05 would be transparent to user (see "LSHM Hermaphroditic connector mating configuration" section above) the LSHM connector's pin numbers would be identical to the host LSHM connector pin numbers as seen from ZX118LSHM-05's J2 connector. Special care must be given if special rework required between the J1 & J2 LSHM connectors pins as the pin 1, 3, 5, 7, 9, .. of J1 LSHM connector are connected to pin 2, 4, 6, 8, 10, .. of the J2 LSHM connector.

Mated Pin Details: Figure 2.2 exhibits LSHM connector family mated pin interface. -DV connectors are Straight, -DH connector series are Right Angle and the -RH are Reverse Right Angle connectors. All LSHM connector series mate with each other. However; attention must be paid to pin to pin interface ensuring expected design interface configuration. Below diagrams are provided as standard pin to pin interface configuration using LSHM Hermaphroditic connector series.

Figure 2.2 – LSHM Mated Pin Details – LSHM connector formactors are: -DV Straight , -DH : Right Angle , -RH : Reverse Right Angle







ALL ZEBAX TECHNOLOGIES DESIGN SPECIFICATIONS, DRAWINGS, PUBLICATIONS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." ZEBAX MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NO INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE

Information furnished is believed to be accurate and reliable. However, Zebax Technologies assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. Specifications mentioned in this publication are subject to change without notice. This publication replaces all other information previously supplied. Zebax Technologies products are not authorized as in life support devices or systematically appeared by the contract of the contract o

ALL ZEBAX products are RoHS compliant and Lead Free unless otherwise indicate

ZEBAX TECHNOLOGIES SANTA CRUZ, CA U.S.A (831) 2 2 2 - 0717 WWW.ZEBAX.COM ASSEMBLY DRAWING SPECIFIED DIMENSIONS ARE INCHES (MM). ITEM: ZX118LSHM-05 DESCRIPTION: Samtec rugged LSHM Hermaphroditic

Razor Beam Breakout Adapter CHECKED: DRAWN:

REVISSION: 1.0 M. MAHIN **KADIJEH** SHEET: 2 OF 3

